



### Features

- cUL, UL, CE, DLC, FCC, RoHS certifications
- Compatible with daylight, camera-detective, occupancy, and infrared Smart Sensors
- Available in UL-listed, frosted one-end or two-end models
- Rotating end caps (0 - 180°)
- 100,000-hour lifetime
- 5-year warranty




### Applications



Residential



Commercial



Hospitality



Retail



Health & Assisted Care

### Specifications

LED	SMD2835	
Type	T8	
Power Consumption	16 W	23 W
Dimmable	No	
CCT	4,000 K / 5,000 K	
Luminous Output	1,600 lm	2,200 lm
CRI	> 83	
Input End	One-end input / Two-end input	
Cover	Milky Frosted	
Input Voltage	100 - 277 V AC	
Luminous Efficacy	135 lm/W	
Dimensions	Length	Ø
	48 in (1,200 mm)	1.02 in (26 mm)

Model Number (One-end Milky Frosted)	Model Number (Two-end Milky Frosted)	Power Consumption	Correlated Color Temperature (CCT)	Luminous Output
BT8I16N4O4F	BT8I16N4T4F	16 W	4,000 K	1,600 lm
BT8I16N5O4F	BT8I16N5T4F		5,000 K	
BT8I23N4O4F		23 W	4,000 K	2,200 lm
BT8I23N5O4F			5,000 K	